

SPECIFICATION

SegriScreen®

Product Code	Description	Wheeled	Height	Width	Colour	Material
FS7288	SegriScreen	Yes	1830mm	1800mm	BL, RD, YL, GN, WT	PES, PI, SS
FS7000	Replacement Screen Material	N/A	1800mm	1800mm	BL, RD, YL, GN, WT	PES
FS7304	SegriScreen	Yes	2250mm	1800mm	BL, RD, YL, GN, WT	PES, PI, SS
FS7004	Replacement Screen Material	N/A	2250mm	1800mm	BL, RD, YL, GN, WT	PES
FS7294	Extension Leg for SegriScreen	N/A	250mm			SS
FS7292	SegriScreen X-TEND	Yes	1830mm	1800mm	BL, RD, YL, GN, WT	PES, PI, SS
FS7002	Replacement X-TEND Screen Material	N/A	1800mm	1800mm	BL, RD, YL, GN, WT	PES
FS7312	SegriScreen X-TEND	Yes	2250mm	1800mm	BL, RD, YL, GN, WT text	PES, SS
FS7006	Replacement X-TEND Screen Material	N/A	2250mm	1800mm	BL, RD, YL, GN, WT	PES
FS7410	SegriScreen SHIELD	No	1830mm	650mm	Clear	PES, SS, PP
FS7420	SegriScreen SHIELD	No	1830mm	850mm	WT, BL, Clear	PES, SS, PP
FS7430	SegriScreen SHIELD	No	1830mm	1050mm	WT, Clear	PES, SS, PP

SegriScreen and SegriScreen X-TEND Colour Options:



Optional printing for customised messaging (black ink only on Blue, Red, Yellow and Green screens).



When not in use, multiple screens easily nest inside each other for safe and compact storage.

Multiple SegriScreen X-TENDs connect to form a mobile, pivotable barrier:



SegriScreen SHIELD Colour Options:



White

(Screen material covers full frame.)



Clear

(Screen material covers top 1300mm of frame. Below knee-height is open.)

Technical Data

Cleaning: Easy to clean down.

Operating Temp: -30°C to +70° (PES Cover).

Assembly: Delivered flatpack with full instructions included for simple assembly. Approximate assembly time is around 10 minutes per screen.

Material - Frame: Grade 304 Stainless Steel, with welded ends for reduced risk of contamination and bacteria harbourage.

Material - Cover: Detachable Polyethersulfone (PES) 1100 d/tex. Gloss and lacquered both sides (5 colour options, plus clear for SegriScreen SHIELD), with stainless steel eyelets.

Material - Wheels: stainless-steel castors with white polyamide wheel.

Material - Fixings: Screen frames attached using stainless-steel 20mm M6 mm frame bolts, with stainless-steel lock-tight washers. SegriScreen SHIELDS use detectable cable ties.

Storage: Screens nest together for easy and compact storage when not in use.

This certificate was prepared on behalf of Klipspringer Ltd and the information included is to the best of our knowledge correct at the time of writing. Klipspringer offers the information within this document as a guide only, they do not represent any guarantee of the prescribed products in the sense of the legal guarantee regulations. It is the responsibility of the end user to ensure the items purchased are suitable for the intended application.

Supplier/Importer	Klipspringer Ltd
Address	Rynor House, Farthing Road, Ipswich, Suffolk, UK. IP1 5AP
Telephone	+44 (0) 1473 461 800
Email	sales@klipspringer.com
Website	www.klipspringer.com